

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the above-referenced application.

Listing of Claims:

1. (Currently amended) A mold assembly for generating a composite part from a strengthener in a generally solid phase and a matrix in a generally liquid phase; said mold assembly comprising:

a) a base mold including a strengthener chamber for receiving the strengthener, a matrix injection inlet for injecting the matrix in said strengthener chamber and an evacuation outlet, said inlet and said outlet defining a propagation direction;

b) a cover mold including a compression chamber defining a compression wall substantially uniformly spaced apart from the composite part to be generated and having a geometry substantially conforming to a configuration of the composite part to be generated, and a fluid control aperture for injecting a controlling fluid in said compression chamber; said cover mold being so configured as to be sealingly mounted on said base mold whereby said strengthener chamber and said compression chamber are adjacent ~~and~~, wherein said controlling fluid is an incompressible fluid; and

c) a deformable member provided in a gap defined by said strengthener chamber and said compression chamber, said deformable member being so configured as to pressurize the matrix toward the strengthener and propagate the matrix along said propagation direction upon compression exerted on said deformable member by the controlling fluid.

2. (Original) A mold assembly as recited in claim 1, wherein said matrix injection inlet includes a diffusion passage provided on a contact wall of said strengthener chamber.

3. (Cancelled)

4. (Previously presented) A mold assembly as recited in claim 1, wherein said evacuation outlet is connectable to a vacuum source to selectively generate at least a partial vacuum in said strengthener chamber.

5. (Currently amended) A mold assembly as recited in claim 1, wherein the base mold includes a contact wall, peripheral walls extending around said contact wall and shoulders extending around said peripheral walls; said cover mold includes ~~[[a]]~~ the compression wall, peripheral walls extending around said compression wall and shoulders extending around said peripheral walls, said cover mold being sealingly mounted to said base mold through a complementary ridge and groove arrangement provided along said shoulders of said base mold and said cover mold.

6. (Original) A mold assembly as recited in claim 5, wherein said ridge and groove arrangement has a generally triangular cross-sectional profile.

7. (Previously presented) A mold assembly as recited in claim 1, wherein said fluid control aperture is connectable to a fluid source to generate pressure in said compression chamber.

8. (Original) A mold assembly as recited in claim 1, wherein said fluid control aperture extends in said cover mold and said matrix injection inlet extends in said base mold in a generally similar direction.
9. (Original) A mold assembly as recited in claim 1, wherein said cover mold includes a vent extending from said compression chamber and through said cover mold.
10. (Original) A mold assembly as recited in claim 9, wherein said vent is connected to a vacuum source to selectively generate at least a partial vacuum in said compression chamber.
11. (Previously presented) A mold assembly as recited in claim 9, wherein said vent comprises a valve to regulate the flow of the controlling fluid through said vent.
12. (Original) A mold assembly as recited in claim 1, wherein said gap has a variable thickness.
13. (Original) A mold assembly as recited in claim 12, wherein said compression chamber has a first thickness, said strengthener chamber has a second thickness, said first and second thickness being variable upon deformation of said deformable member.
14. (Original) A mold assembly as recited in claim 1, wherein said deformable member includes a membrane sealingly mounted between said strengthener chamber and said compression chamber.

15. (Currently amended) A mold assembly as recited in claim ~~[[1]]~~ 14, wherein said membrane is impermeable to liquid.

16. (Currently amended) A mold assembly as recited in claim ~~[[1]]~~ 14, wherein said membrane is permeable to gas.

17. (Cancelled)

18. (Original) A mold assembly as recited in claim 1, wherein said mold assembly includes temperature controlling means.

19. (Previously presented) A mold assembly as recited in claim 1, wherein said strengthener chamber comprises a contact wall for locating the strengthener, said contact wall having a controlled surface finish.

20. (Original) A mold assembly as recited in claim 1, wherein said base mold and said cover mold are rigid.

21. (Original) A mold assembly as recited in claim 1, wherein said deformable member includes a deformable element and a membrane, said membrane being sealingly mounted between said strengthener chamber and said compression chamber, said deformable element being provided in at least a portion of said compression chamber.

22. (Original) A mold assembly as recited in claim 21, wherein a surface of said deformable element is so machined as to be complementary to the shape of the composite part.

23. (Currently amended) A mold assembly as recited in claim 22, wherein said machined surface of said ~~member~~ deformable element includes a series of grooved channels so configured as to receive said membrane.

24. (Original) A mold assembly as recited in claim 21, wherein said deformable element is injected directly into said gap via said fluid control aperture.

25. (Original) A mold assembly as recited in claim 21, wherein said deformable element includes a generally porous and elastic material.

26. (Original) A mold assembly as recited in claim 1, wherein said deformable member includes an elastic material being provided in at least a portion of said compression chamber and adjacent to said strengthener chamber.

27. (Original) A mold assembly as recited in claim 1, wherein said cover mold includes compartmentalized portions so configured as to independently move with respect to one another toward and away from said strengthener chamber for providing a gap of variable thickness.

28. (Original) A mold assembly as recited in claim 1, wherein said mold assembly further includes a tube provided in said compression chamber and adjacent to said strengthener chamber, said tube being connected to a pressure source and deformable under pressure generated from the pressure source, said tube including at least one extremity mounted through said cover mold for controlling the pressure in said tube.

29. (Currently amended) A mold assembly as recited in claim 1, wherein said cover mold includes [[a]] the compression wall including a plurality of passages provided adjacent to said deformable member.

30. (Original) A mold assembly as recited in claim 29, wherein said plurality of passages includes longitudinal passages and transversal passages configured in a grid so as to cooperate with said deformable member.

31. (Original) A mold assembly as recited in claim 29, wherein said matrix injection inlet of said base mold includes a diffusion passage extending on a contact wall of said strengthener chamber; said diffusion passage being generally aligned with at least one transversal passage and said matrix injection inlet of said base mold being generally aligned with at least one longitudinal passage.

Claims 32 - 44 (Cancelled).

45. (Currently amended) A mold assembly for generating a composite part from a strengthener and a matrix; said mold assembly comprising:

a) a base mold including a strengthener chamber for receiving the strengthener, a matrix injection inlet for injecting the matrix in said strengthener chamber and an evacuation outlet, said inlet and said outlet defining a propagation direction;

b) a cover mold including a compression chamber defining a compression wall substantially uniformly spaced apart from the composite part to be generated and having a geometry substantially conforming to a configuration of the composite part to be generated, and a fluid control aperture for injecting a controlling fluid in said compression chamber; said cover mold being so configured as to be sealingly mounted on said base mold whereby said strengthener chamber and said compression chamber are adjacent and, wherein said controlling fluid is an incompressible fluid; and

c) a deformable member provided in a gap defined by said strengthener chamber and said compression chamber, said deformable member generating a deformation zone in said compression chamber from a portion of the matrix permeating the strengthener, said deformable member being pressurized by the controlling fluid in proximity of said deformation zone for redirecting the portion of matrix generating said deformation zone back to the strengthener and for propagating the matrix along said propagation direction.

Claims 46 - 69 (Cancelled).

70. (Previously presented) A mold assembly as recited in claim 1, wherein said deformable member is able to be swollen in said compression chamber from the matrix permeating the strengthener to generate a deformation zone, said deformable member receiving pressure from the controlling fluid in proximity of said deformation zone for redirecting the matrix towards the strengthener.

71. (Previously presented) A mold assembly as recited in claim 1, wherein said deformation zone is adjacent to a matrix flow front corresponding to a portion of the strengthener impregnated by the matrix, said matrix flow front propagating in the strengthener along said propagation direction as the matrix in said deformation zone is redirected to the strengthener.

Claims 72 - 75 (Cancelled).

76. (New) A mold assembly as recited in claim 1, wherein said mold assembly includes a porous medium provided in said compression chamber for controlling the propagation of the fluid injected in said compression chamber.

77. (New) A mold assembly as recited in claim 76, wherein said porous medium is made from a generally deformable element.